

**AMENDMENTS TO THE CLAIMS:**

Claims 1 and 2: (Canceled):

3. (Previously presented): A method according to claim 23, wherein the analysis comprises calculation of the rate of change in the reducing milk flow rate in order to determine step changes in the milk flow rate.

4. (Previously presented): A method according to claim 23, wherein the predicted stepped reduction in the milk flow rate includes four step changes corresponding to the milk flow from respective teats falling at the end of milking.

Claim 5: (Canceled):

6. (Previously presented): A method according to claim 25, wherein a ratio of the peak flow duration to the peak flow rate is calculated and selecting the animal for medical inspection is dependent on the calculated ratio value exceeding a predicted value.

7. (Previously presented): A method according to claim 25, wherein the peak flow rate and the duration at the peak flow rate are respectively compared with predicted values, the animal being selected for medical inspection when the peak flow rate departs significantly from the predicted peak flow rate but the peak flow duration remains within acceptable limits of the predicted peak flow duration.

Claim 8: (Canceled):

9. (Previously presented): A method according to claim 23, wherein the predicted relationship between the milk flow rate and the time from commencement of milking

for an animal is derived from data collected during one or more previous milkings of the same animal.

Claims 10 and 11: (Canceled):

12. (Previously presented): An apparatus according to claim 24, wherein the data receiving and analyzing device is arranged to calculate the rate of change in the reducing milk flow rate in order to determine step changes in the milk flow rate.

13. (Previously presented): An apparatus according to claim 24, wherein the data receiving and analyzing device counts the number of steps in the reducing milk flow rate and generates a signal if less than four steps are counted.

Claim 14: (Canceled):

15. (Previously presented): An apparatus according to claim 26, wherein the data receiving and analyzing device calculates a ratio of the peak flow duration to the peak flow rate and generates an output when the calculated ratio exceeds a predicted value by a predetermined amount.

16. (Previously presented): An apparatus according to claim 15, wherein the data receiving and analyzing device compares the peak flow rate and the duration at the flow rate with respective predicted values, and generates an output when the peak flow rate deviates significantly from the predicted peak flow rate but the peak flow duration remains within acceptable limits of the predicted peak flow duration.

17. (Previously presented): An apparatus according to claim 24, wherein the data receiving and analyzing device includes a memory for storing the predicted relationship between

the milk flow rate and the time from commencement of milking for an animal derived from data collected during one or more previous milkings of the same animal.

18. (Previously presented): A apparatus according to claim 24, wherein the milk flow meter includes means to collect and compress milk flow data into data packages and to transfer the data packages to the data receiving and analyzing device at intervals.

19. (Previously presented): An apparatus according to claim 18, wherein the data receiving and analyzing device receives data packages from at least two milk meters and includes means for decompressing the data packages for analysis and/or display of the data.

20. (Currently amended): A method according to ~~any one of~~ claim 23, wherein milking conditions, namely the milking vacuum level, the period of hormone stimulation preparatory to milking, and/or the time of teat cup detachment at the end of milking, for a subsequent milking of the animal are determined in accordance with milk flow rate data generated during the milking of the same animal.

Claims 21 and 22: (Canceled):

23. (Currently amended): A method of milking animals comprising measuring the total milk flow from all the teats of the udder of an animal being milked, the respective milk flows from the respective teats being brought together and the total milk flow being measured using a single milk meter device ~~adapted for generating~~ which generates data representative of the measured total milk flow rate, and analyzing said data using an analyzer device to detect an abnormal milk flow from ~~one~~ a single teat indicated by a predetermined departure from a predicted relationship between the milk flow rate and the time from commencement of milking and generate an output in response to said departure signaling that medical inspection of the

animal is advisable, wherein the detected departure is a departure from a predicted stepped reduction in the milk flow rate towards the end of the milking procedure for the animal.

24. (Currently amended): An apparatus for milking animals comprising, a milk meter device ~~adapted for measuring~~ which measures the total milk flow from all the teats of the udder of an animal being milked and ~~generating~~ generates data representative of the measured total milk flow rate, and an analyzer device ~~for receiving~~ which receives said data and ~~analyzing~~ analyzes the data to detect an abnormal milk flow from one teat indicated by a predetermined departure from a predicted relationship between the milk flow rate and the time from commencement of milking and generate an output in response to said departure signaling that medical inspection of the animal is advisable, wherein the detected departure is a departure from a predicted stepped reduction in the milk flow rate towards the end of the milking procedure for the animal.

25. (Previously presented): A method of milking animals as set forth in claim 23, wherein the analysis includes determining a peak flow rate at which the flow rate remains substantially level for a major part of the animal milking procedure, and determining the duration of the milk flow at the peak flow rate.

26. (Previously presented): An apparatus for milking animals as set forth in claim 24, wherein the milk meter device and the analyzer device generate and analyze data to determine a peak flow rate at which the flow rate remains substantially level for a major part of the animal milking procedure, and determines the duration of the milk flow at the peak flow rate.